



## STEAM GENERATOR

# STEAM BOX VAC INDUSTRIAL

### Body material

Stainless steel AISI 304 (BA)

### Boiler material

Stainless steel AISI 304

(with interchangeable heating element)

### Boiler volume

11 L - 12,5 L

### Tanks

Water: 20 L | Det: 20 L

### Maximum output

11,1 - 15,8 - 22,15 kW

### Boiler output

10 - 14,4 - 20,75 kW

### Steam production

291 - 388 - 564 g/min

17,5 - 23 - 33,8 Kg/h

### Power supply

3~ 400V - 50/60 Hz

### Steam T°

183° C

### Detergent T°

90° C - 160° C

### Vacuum output

1 kW

### Vacuum drum capacity

7,5 L

### Air flow

200 m3/h

### Depression

2200 mm

### Power cord

8 m

### Weight


113 Kg

### Packaging

115x65x125 cm



induction turbine



### APPLICATIONS



**Three-phase steam generator for usage in the industrial sector**, with a stainless-steel body (watertight protection IPX5), **unlimited steam autonomy** thanks to the automatic refilling system with either an internal water tank (electromechanical water level control system inside the boiler – True Temp™) or directly with a water mains connection. **Possibility to inject detergent or hot water together with steam**. **Equipped with an integrated wet&dry vacuum cleaner with an induction turbine**. The steam generator's front panel is **equipped with an electric console with commands for a timer, a thermometer and a pressure gauge**; the digital display will advise the user about the necessity to proceed with the boiler maintenance.



## TOOLS



**GEYSER I 10 BAR**  
Steam 183°C



**RADAMES 10 BAR**  
Steam&vacuum 183°C

